



These lightweight hooks and tie-downs are used with light lines and elastic shock cord in a variety of applications. They provide a quick and economical means of securing lines, sails and other gear.

| PRODUCT No. | DESCRIPTION                                | MAX LINE DIAM. |         | FASTENING HOLE DIAM. |        | WEIGHT |       |
|-------------|--|----------------|---------|----------------------|--------|--------|-------|
|             |  | mm             | (in.)   | mm                   | (in.)  | g      | (oz)  |
| PNP3        | Lacing hook                                | 5              | (3/16)  | 4                    | (5/32) | 3      | (0.1) |
| PNP5        | Snap fairlead                              | 8              | (5/16)  | 4                    | (5/32) | 8      | (0.3) |
| PNP13A      | Narrow snap hook                           | 10             | (3/8)   | -                    | -      | 5      | (0.2) |
| PNP13B      | Narrow snap hook                           | 5              | (3/16)  | -                    | -      | 3      | (0.1) |
| PNP13D      | 'D' snap hook, wide opening                | Webbing 26     | (1)     | -                    | -      | 5      | (0.2) |
| PNP16       | Flag clip                                  | 9              | (11/32) | -                    | -      | 5      | (0.2) |
| PNP38B      | Deck fairlead                              | 4              | (5/32)  | 4                    | (5/32) | 7      | (0.3) |
| PNP45       | Deck hook                                  | 10             | (3/8)   | 4                    | (5/32) | 3      | (0.1) |
| PNP56       | Snap hook, 51mm (2") long                  | -              | -       | -                    | -      | 12     | (0.4) |
| PNP56A      | Ocky strap, 450mm (18") long               | 6              | (1/4)   | -                    | -      | 34     | (1.2) |
| PNP56B      | Snap hook, 45mm (1 3/4") long              | 4              | (5/32)  | -                    | -      | 6      | (0.2) |
| PNP70       | Sail furling/Reefing tie, 450mm (18") long | 5              | (3/16)  | -                    | -      | 47     | (1.2) |
| PNP84       | Jiffy reefing hook                         | 5              | (3/16)  | 5                    | (3/16) | 5      | (0.2) |
| PNP107      | Snap-on hook                               | 5              | (3/16)  | 5                    | (3/16) | 8      | (0.3) |
| PNP108      | Snap-on eye                                | 8              | (5/16)  | 5                    | (3/16) | 8      | (0.3) |
| RF88        | Thumb cleat, Stainless Steel               | 8              | (5/16)  | 5                    | (3/16) | 13     | (0.5) |
| RF6010      | Utility line hanger                        | 5              | (3/16)  | 5                    | (3/16) | 7      | (0.2) |



Hinges are made from quality materials and are suitable for interior and exterior applications.

Plastic cabinet hinges are precision moulded in premium grade UV stabilised resins for strength and have Stainless Steel pins.

Metal hinges are manufactured from Grade 316 Stainless Steel.

PNP116, PNP117 and PNP118 are light duty hinges made from fatigue resistant polypropylene.

The RF2140 locker catch in chrome plated Bronze is recommended for interior use only.

The RF3190 buckle is suitable for 50mm (2") webbing.

Stainless Steel springs are used to keep blocks in an upright position and off the deck.

| PRODUCT No.    | DESCRIPTION  | LENGTH X WIDTH |                 | WEIGHT |       |
|----------------|--|----------------|-----------------|--------|-------|
|                |  | mm             | (in.)           | g      | (oz)  |
| PNP68          | Nylon hinge  | 38 x 38        | (1 1/2 x 1 1/2) | 8      | (0.3) |
| PNP68A         | Nylon hinge  | 51 x 29        | (2 x 1 1/8)     | 5      | (0.3) |
| PNP68B         | Nylon hinge  | 76 x 42        | (3 x 1 5/8)     | 15     | (0.5) |
| PNP68C         | Nylon hinge  | 100 x 53       | (4 x 2 1/8)     | 31     | (1.1) |
| PNP68D         | Nylon hinge, under/over configuration  | 41 x 40        | (1 5/8 x 1 5/8) | 8      | (0.3) |
| PNP89          | Nylon cupboard latch   | Base 47 x 15   | (1 3/4 x 9/16)  | 8      | (0.3) |
| PNP91          | Nylon cupboard latch, right angle  | Base 32 x 13   | (1 1/4 x 1/2)   | 4      | (0.1) |
| PNP116         | Polypropylene hinge, one-piece flexible  | 31 x 29        | (1 1/4 x 1 1/8) | 2      | (0.1) |
| PNP117         | Polypropylene hinge, one-piece flexible  | 40 x 36        | (1 5/8 x 1 3/8) | 3      | (0.1) |
| PNP118         | Polypropylene hinge, one-piece flexible  | 50 x 45        | (2 x 1 3/4)     | 5      | (0.2) |
| RF308          | Pressed Stainless Steel hinge  | 61 x 32        | (2 3/8 x 1 1/4) | 20     | (0.7) |
| RF309          | Pressed Stainless Steel hinge  | 104 x 32       | (4 x 1 1/4)     | 30     | (1.1) |
| RF2140         | Chromed Bronze locker latch  | 52 x 44        | (2 x 1 3/4)     | 68     | (2.4) |
| RF2295         | Hatch lock   | 120 x 50       | (4 3/4 x 2)     | 104    | (3.7) |
| RF2296         | Hatch lock   | 93 x 30        | (3 5/8 x 1 1/8) | 56     | (1.9) |
| RF3190         | Stainless Steel buckle to suit 50mm webbing  | 67 x 47        | (2 5/8 x 1 7/8) | 110    | (3.8) |
| <b>Springs</b> |  |                |                 |        |       |
| RF318          | Tapered. 22mm (7/8") height x 16.5mm (21/32") diameter. 1.2mm (3/64") material diameter  |                |                 | 3      | (0.1) |
| RF319          | 32mm (1 1/4") height x 20mm (25/32") diameter. 2mm (5/64") material diameter             |                |                 | 3      | (0.1) |
| RF320          | 29mm (1 1/8") height x 28mm (1 1/8") diameter. 2.9mm (1/8") material diameter            |                |                 | 15     | (0.5) |
| RF321          | Tapered. 40mm (1 9/16") height x 28mm (1 1/8") diameter. 2mm (5/64") material diameter   |                |                 | 9      | (0.3) |
| RF322          | Tapered. 31mm (1 1/4") height x 28mm (1 1/8") diameter. 1.6mm (1 1/6") material diameter |                |                 | 5      | (0.2) |



Strong, UV resistant Nylon and plastic resins are used to manufacture these general boating accessories, to avoid the scratching of paint and gelcoat often caused by their metal equivalents.

The mast step is manufactured from Stainless Steel and features an aggressive non-slip top surface.

The PNP206 transom step/handle is moulded in a strong, fibre reinforced Nylon which is UV and impact resistant for a long service life. The foot pad area has a textured surface for a sure grip even when wet.

| PRODUCT No.                      | DESCRIPTION   | WEIGHT<br>g (oz) |
|----------------------------------|---|------------------|
| <b>Rings – Nylon</b>             |   |                  |
| PNP53A                           | 17.5mm (11/16") ID, 4mm (5/32") material diameter   | 2 (0.1)          |
| PNP12                            | 17.5mm (11/16") ID, 7mm (9/32") material diameter   | 3 (0.1)          |
| PNP52C                           | 19.5mm (3/4) ID, 5mm (3/16") material diameter  | 2 (0.1)          |
| PNP53D                           | 26mm (1") ID, 6mm (1/4") material diameter  | 3 (0.1)          |
| PNP52B                           | 31mm (1 1/4") ID, 7.9mm (5/16") material diameter   | 7 (0.3)          |
| PNP11                            | 32.5mm (1 1/4") ID, 6.5mm (1/4") material diameter  | 4 (0.1)          |
| PNP53E                           | 43.5mm (1 3/4") ID, 9.5mm (3/8") material diameter  | 13 (0.5)         |
| <b>Tube Clips – Nylon</b>        |   |                  |
| PNP43A                           | Suits 44mm (1 3/4") OD tube   | 15 (0.6)         |
| PNP43B                           | Suits 38mm (1 1/2") OD tube   | 10 (0.4)         |
| PNP43C                           | Suits 32mm (1 1/4") OD tube   | 7 (0.3)          |
| PNP43D                           | Suits 25mm (1") OD tube   | 4 (0.1)          |
| PNP43E                           | Suits 16mm (5/8") OD tube   | 4 (0.1)          |
| PNP43F                           | Suits 19mm (3/4") OD tube   | 4 (0.1)          |
| <b>Rowlocks &amp; Boat Hooks</b> |   |                  |
| PNP4                             | Spinnaker/Whisker pole end, 25mm (1") OD  | 14 (0.5)         |
| PNP26                            | Boat hook, nylon. Suits 25mm (1") OD tube   | 48 (1.7)         |
| PNP77                            | Rowlock & Plate, suits oars or oar stops 51mm (2") diameter                                 | 53 (1.9)         |
| <b>Steps &amp; Handles</b>       |   |                  |
| PNP206                           | Transom step/handle 165mm (6 1/2")  | 140 (4.9)        |
| PNP207                           | Handle 140mm (5 1/2") screw-on  | 50 (1.8)         |
| PNP208                           | Carry handle 145mm (5 3/4") screw-on  | 35 (1.2)         |
| PNP172                           | Carry handle 115mm (4 1/2"), White  | 70 (2.5)         |
| PNP172BLK                        | Carry handle 115mm (4 1/2"), Black  | 70 (2.5)         |
| RF6092                           | Mast step / halyard organiser. Stainless Steel. Non-slip diamond pattern for secure footing | 85 (3)           |