



RF2006
RF2009

RF2053

RF2054



RF2014B



RF2014W



RF2094



RF2102



RF2102W



RF2075



RF2048



RF2048SB



RF2010



RF2035



RF2036



RF2040




RF2082

This range of lights includes riding and anchor lights in a variety of mounting configurations.

They are manufactured from highest quality materials including UV stabilised and impact resistant polymers and Stainless Steel for long and reliable service.

O-Rings, gaskets and seals are incorporated to guarantee water tight integrity and readily available globe are utilised to facilitate ease of service.

The RF2014 side lights feature a unique indicator window to confirm globe operation from the back of the light.



PRODUCT No.	DESCRIPTION	WEIGHT g (oz)
RF2006	Anchor light, 360° arc, 610mm (24") pole	300 (10.6)
RF2009	Anchor light, 360° arc, 762mm (30") pole	370 (13.0)
RF2010	Retractable (through-deck) pole-light base, Chrome Plated Bronze	275 (9.0)
RF2014B	Side light set, black housing, 1 x Port (red) & 1 x Starboard (green), base: 125mm x 51mm (5" x 2"), height: 51mm (2")	225 (8.0)
RF2014W	Same as RF2014B, but with white housing	225 (8.0)
RF2035	Globe, Festoon 36mm, 12V x 10W, suits RF2014, RF2102	2 (0.1)
RF2036	Globe, Bayonet 36mm, 12V x 10W, suits RF2004, RF2006, RF2009, RF2053, RF2054, RF2075, RF2082, RF2094	4 (0.1)
RF2040	Lens, suits RF2006, RF2009, RF2053, RF2054, RF2075, RF2082, RF2094	24 (0.8)
RF2048	Pivoting base, Chrome Plated Bronze, positive wing nut locking, multi-angle positioning	270 (9.5)
RF2048SB	Star bolt only, to suit RF2048	40 (1.4)
RF2053	Anchor light, 360° arc, 610mm (24") pole and pivoting base	580 (20.5)
RF2054	Anchor light, 360° arc, 610mm (24") pole and through-deck base	575 (20.3)
RF2075	Anchor light, 360° arc, horizontal mount	80 (2.8)
RF2082	Anchor light, 360° arc, with vertical mount bracket	110 (3.9)
RF2094	Anchor light, 360° arc, pedestal base, 140mm (5 1/2") High	28 (1.0)
RF2102	Stern light, 135° arc, black housing, transom mount	100 (3.5)
RF2102W	Same as RF2102, but white housing	100 (3.5)



RF2030 and RF2031 masthead lights incorporate a wind indicator socket and an O-Ring sealed, bayonet assembly to ensure watertight integrity and facilitate servicing and installation.

Dry cell battery navigation lights are ideal for use on small craft that don't have permanent electrical systems, or as auxiliary/back-up lights on larger craft that do.

RF2118 and RF2119 have mounting facilities for permanent installation or can be easily detached when required.

Battery powered lights are for emergency use only.

PRODUCT No.	DESCRIPTION	WEIGHT	
		g	(oz)
RF2030	Masthead tri-colour light. Incorporates red and green side lights, and white stern light. Long life 20watt Quartz Halogen globe. Base: 88mm (3 1/2") diam. Height: 167mm (6 1/2")	400	(14.0)
RF2031	Combination masthead tri-colour and anchor/steaming light. Same as RF2130, but with additional lower all round white light. Lower light globe is 10watt. Base: 88mm (3 1/2") diam. Height: 257mm (10")	640	(22.0)
RF2034	Globe, Halogen 12V x 10W, suits RF2031 anchor	6	(0.1)
RF2037	Globe, Halogen 12V x 20W, suits RF2030, RF2031 tri-colour	5	(0.2)
RF2038	Globe, Festoon 11mm, 3V x 0.75W, suits RF2118, RF2119 bi-colour	2	(0.1)
RF2039	Globe, Edison screw, 2.5V x 0.22A, suits RF2119, RF2131 anchor	6	(0.1)
RF2118	Port/Starboard light. Takes two size 'D' batteries in self contained case. On/off switch at rear. Supplied with mounting plate. Overall dimensions 152 x 89 x 64mm (6" x 3 1/2" x 2 1/2")	240	(8.5)
RF2119	Port/Starboard light and 360° white riding light. Independent light sources and switching. Supplied with mounting plate. Takes two size 'D' batteries inside Port/Starboard case and one size 'D' battery in riding case. Overall dimensions 152 x 89 x 356mm (6" x 3 1/2" x 14")	340	(12.0)
RF2131	360° white riding light. Simply rotate lens on housing to activate on/off switch. Takes one size 'D' battery inside case. Water tight O-Ring seal. Provision for attachment to halyard for hoisting to required height	95	(3.4)