

Series 50 All Purpose blocks are typically used on boats up to 10 metres (33 feet) for main and spinnaker sheets, halyards and other primary applications. Load ratings for these blocks are exceptionally high for their size, starting at 750kg (1650lb) for the All Purpose single.

UV stabilised Acetal sheaves provide bearing performance on a polished Stainless Steel race

that performs equally well with dynamic and static loads, to provide maximum durability and a long service life.

Captive Lock™ universal heads allow the blocks to be fixed in either of two planes, or free to swivel as required. Double and triple block heads have a set screw for this adjustment.

Becket pins are removable so lines can be spliced prior to fitting, and are ingeniously locked into position without the use of clevis pins, split rings or tools.

Shackles have slotted pins to avoid fouling lines.




▶ RF150

4.8mm (3/16") pin suits
single and fiddle blocks

▶ RF151

6mm (1/4") pin suits
double and triple blocks



▶ RF51010

snap-in keyhole
becket pin and roller



▶ RF51011

becket pin, roller
and split ring

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		MWL		BL		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
AP All Purpose													
RF51100	Single block, universal head	50	(2)	12	(1/2)	5	(3/16)	750	(1650)	1500	(3310)	118	(4.2)
RF51101	Single block, loop head	50	(2)	12	(1/2)	-	-	750	(1650)	1500	(3310)	98	(3.5)
RF51110	Single block, becket, universal head	50	(2)	12	(1/2)	5	(3/16)	750	(1650)	1500	(3310)	134	(4.7)
RF51111	Single block, becket, loop head	50	(2)	12	(1/2)	-	-	750	(1650)	1500	(3310)	114	(4.0)
RF51200	Double block, universal head	50	(2)	12	(1/2)	6	(1/4)	1000	(2200)	2000	(4410)	255	(9.0)
RF51210	Double block, becket, universal head	50	(2)	12	(1/2)	6	(1/4)	1000	(2200)	2000	(4410)	271	(9.5)



RF51300



RF51500



RF2450



RF51510



RF51530

Fiddle blocks are used to create direct purchase systems for mainsheet, boom vang and other applications.

The easily adjusted cleat arms are just one of the Smart Features™ that make Ronstan blocks so versatile. The sliding posts are simply pulled out of the stops to adjust (no tools required), and then snap back into the locked position to secure the arms.

The stand-up adapter suits all Series 50 single and fiddle blocks.

SMART FEATURES™

- ▶ Exceptionally high working loads
- ▶ Low maintenance, long service life
- ▶ Removable becket pins
- ▶ Captive Lock™ universal head fitting
- ▶ Quick adjusting cleat arms

MATERIALS

- ▶ UV stabilised Acetal sheaves
- ▶ Impact modified, fibre reinforced and UV stabilised Zytel® cheeks
- ▶ Grade 316 Stainless Steel load straps and head fittings

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm	MAX. ROPE (in.)	PIN DIAM. mm (in.)	MWL kg (lb)	BL kg (lb)	WEIGHT g (oz)
AP All Purpose							
RF51300	Triple block, universal head	50	(2) 12 (1/2)	6 (1/4)	1200 (2650)	2400 (5290)	369 (13.0)
RF51500	Fiddle block, universal head	54 + 34	(2 1/8 + 1 5/16) 10 (3/8)	5 (3/16)	750 (1650)	1500 (3310)	167 (5.9)
RF51510	Fiddle block, becket, universal head	54 + 34	(2 1/8 + 1 5/16) 10 (3/8)	5 (3/16)	750 (1650)	1500 (3310)	176 (6.2)
RF51530	Fiddle block, becket, adj. cleat, universal head	54 + 34	(2 1/8 + 1 5/16) 10 (3/8)	5 (3/16)	750 (1650)	1500 (3310)	318 (11.2)
AP Accessories							
RF2450	Stand-Up Base 51x75mm (2"x3") base	-	- - -	5 (3/16)	500 (1100)	1000 (2200)	77 (2.7)



RF6170



RF6171




RF1378

5mm (3/16") → ←



RF1379

5mm (3/16") → ←



RF998



RF1380

5mm (3/16") → ←

Adapters add to the versatility of Series 50 blocks, allowing easy conversion to snap-shackle head, stand-up, or genoa sheet lead applications. Snap shackle adapters fit the head posts of single and fiddle blocks, and are available in standard swivel and trunnion versions.

The RF998 slider adapter suits 25mm (1") T-Track. (See page 56 for further details) Upright lead blocks and cheek blocks keep lines organised and close to the deck. The single cheek block is also available with a curved base for mounting on masts and booms.

- MATERIALS**
- ▶ UV stabilised Acetal sheaves
 - ▶ Fibre reinforced Nylon cheeks
 - ▶ Grade 316 Stainless Steel load straps and housings
 - ▶ Snap Shackle Adapters: 15-5PH investment cast Stainless Steel

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm (in.)	MAX. ROPE mm (in.)	PIN DIAM. mm (in.)	MWL kg (lb)	BL kg (lb)	WEIGHT g (oz)
AP All Purpose							
RF1378	Cheek block, flat base	50 (2)	12 (1/2)	- -	500 (1100)	1000 (2200)	115 (4.1)
RF1379	Cheek block, curved base	50 (2)	12 (1/2)	- -	500 (1100)	1000 (2200)	115 (4.1)
RF1380	Cheek block, double, flat base	50 (2)	12 (1/2)	- -	500 (1100)	1000 (2200)	180 (6.4)
Accessories							
RF998	25mm T-track slide with block head adapter, loaded track stop	- -	- -	5 (3/16)	750 (1650)	1500 (3310)	167 (5.9)
RF6170	Snap shackle head adapter	- -	- -	5 (3/16)	750 (1650)	1500 (3310)	49 (1.7)
RF6171	Trunnion snap shackle head adapter	- -	- -	5 (3/16)	565 (1240)	1135 (2500)	62 (2.2)