



RF1088
RF1088AW



RF1096



RF1089



RF1097

Series 75 All Purpose blocks share many of the same features of the Series 60 blocks and are ideal for larger cruising yachts.

Strength and reliability are achieved through the use of a dependable, self

lubricating Oilite Bronze bearing system and Grade 316 Stainless Steel load straps and cheeks. The black chromed cheeks are flared at rope entry and exit points to minimise chafing.

Impact resistant Acetal sheaves, or anodised Aluminium sheaves for wire (AW versions) run on self-lubricating Oilite Bronze bearings and can be removed for servicing.

| PRODUCT No. | DESCRIPTION | SHEAVE DIAM. mm (in.) | MAX. ROPE mm (in.) | MAX. WIRE mm (in.) | MWL kg (lb) | BL kg (lb) | WEIGHT g (oz) |
|-----------------------|--|-----------------------|--------------------|--------------------|-------------|-------------|---------------|
| AP All Purpose | | | | | | | |
| RF1088 | Single block, universal head | 75 (3) | 14 (9/16) | - - | 1500 (3300) | 3800 (8360) | 545 (19.3) |
| RF1088AW | Single block, universal head, alum. rope/wire sheave | 75 (3) | 14 (9/16) | - - | 1500 (3300) | 4000 (8800) | 345 (12.2) |
| RF1089 | Single block, becket, universal head | 75 (3) | 14 (9/16) | - - | 1500 (3300) | 3000 (6600) | 1265 (44.7) |
| RF1096 | Double block, universal head | 75 (3) | 14 (9/16) | - - | 1500 (3300) | 3000 (6600) | 905 (32.0) |
| RF1097 | Double block, becket, universal head | 75 (3) | 14 (9/16) | - - | 1500 (3300) | 3000 (6600) | 520 (18.3) |



Double and triple blocks can be used to create multiple purchase systems for mainsheets and other applications.

The RF1080 is a low profile block for applications that do not require articulation in the head fitting. A snap shackle head swivel block is also available.

The RF1100 stand up block features a diamond shaped deck plate for close positioning when fitted near the mast for halyard leads.

MATERIALS

- ▶ UV stabilised Acetal sheaves

- ▶ Anodised aluminium sheaves (AW versions)
- ▶ Grade 316 Stainless Steel load straps and head fittings
- ▶ Black chromed Grade 316 Stainless Steel cheeks



▶ RF618 – 7.9mm (5/16") pin

| PRODUCT No. | DESCRIPTION | SHEAVE DIAM. | | MAX. ROPE | | MAX. WIRE | | MWL | | BL | | WEIGHT |
|-----------------------|---|--------------|-----------|-----------|----------|-------------|-------------|-------------|--------|----|--|--------|
| | | mm (in.) | mm (in.) | mm (in.) | mm (in.) | kg (lb) | kg (lb) | kg (lb) | g (oz) | | | |
| AP All Purpose | | | | | | | | | | | | |
| RF891 | Single block, snap shackle head | 75 (3) | 14 (9/16) | - | - | 1500 (3300) | 3800 (8360) | 545 (19.3) | | | | |
| RF1080 | Single block, bolt head | 75 (3) | 14 (9/16) | - | - | 1500 (3300) | 4000 (8800) | 345 (12.2) | | | | |
| RF1081 | Triple block, cleat, becket (rivet), universal head | 75 (3) | 14 (9/16) | - | - | 1500 (3300) | 3000 (6600) | 1265 (44.7) | | | | |
| RF1082 | Triple block, universal head | 75 (3) | 14 (9/16) | - | - | 1500 (3300) | 3000 (6600) | 905 (32.0) | | | | |
| RF1100 | Stand-up block | 75 (3) | 14 (9/16) | - | - | 1500 (3300) | 3000 (6600) | 520 (18.3) | | | | |



BLOCKS – AP All Purpose



This range of robust blocks features a universal head for fixing in one of several positions or leaving the block free to swivel.

The anodised Aluminium sheave runs on a self-lubricating Oillite Bronze bearing. Sheaves are removable for servicing.

For long term strength and dependability, Series 100 blocks feature Grade 316 Stainless Steel load straps and cheeks, black chromed and flared to minimise rope chafing.

MATERIALS

- ▶ Anodised aluminium sheaves
- ▶ Grade 316 Stainless Steel load straps and head fittings
- ▶ Black chromed Grade 316 Stainless Steel cheeks

▶ RF619 – 9.5mm (3/8") pin

| PRODUCT No. | DESCRIPTION | SHEAVE DIAM. | | MAX. ROPE | | MWL | | BL | | WEIGHT | |
|----------------|-------------------------------------|--------------|-------|-----------|-------|------|--------|------|--------|--------|------|
| | | mm | (in.) | mm | (in.) | kg | (lb) | kg | (lb) | g | (oz) |
| AP All Purpose | | | | | | | | | | | |
| RF1065 | Single block, universal head | 102 | (4) | 18 | (3/4) | 2200 | (4840) | 4400 | (9680) | 1170 | (41) |
| RF1066 | Single block becket, universal head | 102 | (4) | 18 | (3/4) | 2200 | (4840) | 4400 | (9680) | 1290 | (46) |
| RF1067 | Double block, universal head | 102 | (4) | 18 | (3/4) | 2200 | (4840) | 4400 | (9680) | 1720 | (61) |