

STAINLESS TRACK

16 & 22mm (5/8 & 7/8")



RF363, RF364, RF365 TRACK PROFILE

Area: 41.6mm²
 Centroid: X = +9.57mm, -9.57mm
 Y = +4.29mm, -3.11mm
 Moments of Inertia: I_{xx} = 215mm⁴
 I_{yy} = 1885mm⁴

Curved track not suitable

RF390 TRACK PROFILE

Area: 61.1mm²
 Centroid: X = +13.35mm, -13.35mm
 Y = +5.70mm, -4.20mm
 Moments of Inertia: I_{xx} = 645mm⁴
 I_{yy} = 5732mm⁴

Curved track not suitable



TRACKS & TRAVELLERS

Stainless Steel track is typically used on dinghies for jib sheet leads and adjustable hiking strap systems. It is also used for adjustable goosenecks and outhauls for its strength, light weight and low profile. Slides feature spring-loaded plungers for fast, positive positioning.

MATERIALS

- ▶ Grade 304 Stainless Steel track
- ▶ Chrome plated Brass slides

▶ **TRACK FASTENINGS** – 5mm (3/16") countersunk fasteners at 76mm (3") centres ▶ **STOP HOLES** – 19mm (3/4") centres

PRODUCT No.	DESCRIPTION	MWL		BL		WEIGHT	
		kg	(lb)	kg	(lb)	g	(oz)
16mm (5/8") Track System							
RF55	Slide with swivelling dead eye, spring-loaded track stop	-	-	-	-	62	(2.2)
RF106	Slide with swivelling dead eye, cam cleat, spring-loaded track stop	-	-	-	-	185	(6.5)
RF363x0.45	Track, 0.45m (18") long					130	(4.6)
RF363x1.5	Track, 1.5m (5') long					435	(15.4)
RF363x3.0	Track, 3.0m (10') long					870	(30.7)
RF364	Track, 0.38m (15") long					110	(3.9)
RF365	Track, 0.3m (12") long					90	(3.2)
RF366	Nylon track end	-	-	-	-	5	(0.2)
RF367	Track stop, spring-loaded	-	-	-	-	20	(0.7)
RF370	Slide with loop	225	(500)	450	(990)	45	(1.6)
RF371	Slide with loop, spring-loaded track stop	225	(500)	450	(990)	70	(2.5)
RF372	Slide with jib sheet fairlead, spring-loaded track stop (Sold as a pair)	-	-	-	-	95	(3.4)
RF373	Slide with dead eye, cam cleat, spring-loaded track stop (Sold as a pair, 1 L/H & 1 R/H)	-	-	-	-	202	(7.1)
22mm (7/8") Track System							
RF390x1.5	Track, 1.5m (5') long					635	(22.4)
RF390x3.0	Track, 3.0m (10') long					1270	(44.9)
RF393	Nylon track end	-	-	-	-	5	(0.2)
RF397	Slide with loop	275	(610)	550	(1210)	85	(3.0)
RF398	Slide with loop, spring-loaded track stop	275	(610)	550	(1210)	115	(4.1)