



Simple, functional and lightweight, the Ronstan range of rudder fittings is designed for precision performance and dependability. Insert moulded Nylon bushes provide a firm fit between gudgeon and pintle, and prevent corrosion and fatigue. Reinforced Nylon, extruded Aluminium and Stainless Steel are used to create strong, reliable fittings with a compact profile and minimum weight.

MATERIALS

- ▶ Black anodised extruded Aluminium alloy rudder gudgeons
- ▶ Fibre reinforced Nylon 66 pintle and transom gudgeons
- ▶ Grade 304 Stainless Steel pintle pins

PRODUCT No.	PIN/HOLE DIAM.		INTERNAL WIDTH		STRAP LENGTH		WEIGHT	
	mm	(in.)	mm	(in.)	mm	(in.)	g	(oz)
Rudder Gudgeons								
RF2500	7.9	(5/16)	20	(25/32)	79	(3 1/8)	42	(1.5)
RF2501	7.9	(5/16)	32	(1 1/4)	96	(3 3/4)	85	(3.0)
RF2502	9.5	(3/8)	32	(1 1/4)	96	(3 3/4)	85	(3.0)
RF2503	7.9	(5/16)	40	(1 9/16)	96	(3 3/4)	85	(3.0)
RF2504	9.5	(3/8)	40	(1 9/16)	96	(3 3/4)	85	(3.0)
RF2505	7.9	(5/16)	50	(2)	96	(3 3/4)	106	(3.7)
RF2506	9.5	(3/8)	50	(2)	96	(3 3/4)	106	(3.7)
Transom Gudgeons								
RF2510	7.9	(5/16)	-	-	-	-	19	(0.7)
RF2511	9.5	(3/8)	-	-	-	-	19	(0.7)
Transom Pintles								
RF2515	7.9	(5/16)	-	-	-	-	47	(1.7)
RF2516	9.5	(3/8)	-	-	-	-	56	(2.0)
Accessories								
PNP55	Rudder gudgeon/pintle retaining clip, transom mount. Nylon		-	-	-	-	5	(0.2)



Fabricated Stainless Steel rudder gudgeons and pintles are robust and reliable. Pins are cross drilled to accept the RF413 retaining clip. Wing nut pivot bolts for rudder blades are easy to adjust in all conditions.

The RF1336 and RF1337 heavy duty gudgeons, with removable clevis pins, are suitable for use on boats up to 8 metres (26 feet).

MATERIALS

- ▶ Grade 316 Stainless Steel
- ▶ Hand Polished Grade 304 Stainless Steel (RF1336 and RF1337)

PRODUCT No.	DESCRIPTION	PIN/HOLE		WIDTH		STRAP LENGTH		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	g	(oz)
RF239	Rudder gudgeon	6	(1/4)	38	(1 1/2)	51	(2)	40	(1.4)
RF243	Rudder gudgeon	6	(1/4)	25	(1)	56	(2 3/16)	35	(1.2)
RF254	Transom gudgeon	6	(1/4)	29	(1 1/8)	-	-	30	(1.1)
RF255	Transom pintle	6	(1/4)	29	(1 1/8)	-	-	45	(1.6)
RF292	Rudder blade pivot bolt 1/4" BSW x 62mm (2 3/8") long, and wing nut	6	(1/4)	-	-	-	-	55	(1.9)
RF314	Transom gudgeon	8	(5/16)	29	(1 1/8)	-	-	55	(1.9)
RF315	Transom pintle	8	(5/16)	29	(1 1/8)	-	-	85	(3.0)
RF316	Rudder pin 8mm (5/16") dia. x 305mm (12") long	8	(5/16)	-	-	-	-	130	(4.6)
RF413	Retaining clip, 2.7mm(3/32") dia. wire. 16mm(5/8") dia. ID	-	-	-	-	-	-	5	(0.2)
RF690	Replacement wing nut, 1/4" BSW thread. Suits RF292	-	-	-	-	-	-	20	(0.7)
RF693	Rudder blade winged pivot bolt, 1/4" BSWx58mm (2 1/4") long	6	(1/4)	-	-	-	-	55	(1.9)
RF1330	Transom gudgeon	10	(3/8)	32	(1 1/4)	-	-	265	(9.4)
RF1331	Transom pintle	10	(3/8)	32	(1 1/4)	-	-	315	(11.1)
RF1332	Rudder gudgeon	10	(3/8)	51	(2)	150	(6)	450	(15.9)
RF1336	Heavy duty transom gudgeon and pin	12.7	(1/2)	35	(1 3/8)	-	-	392	(13.8)
RF1337	Heavy duty rudder gudgeon	12.7	(1/2)	36	(1 7/16)	189	(7 1/2)	472	(16.7)
RF2520	Retaining clip, 2.3mm (3/32") dia. wire	-	-	-	-	-	-	4	(0.1)