



Ronstan stanchions are made from quality grade 316 Stainless Steel and are available in the three most popular sizes. The heights and hole centres conform to most Yacht Racing Rules. Stanchion bases are available in the vertical and 5° off.

PNP209R and PNP209GRN are designed to fit over lifelines or on the wire rigging above the spreaders to help prevent sail chafe and assist in the skirting of the Genoa or large headsails. They are delivered in two pieces enabling them to be snap-fitted on existing lifelines or rigging. Included are plastic grommets that can keep

the roller in a set position on some wire sizes. They are available in red and green.

PNP54 is a strong plastic guard rail or stanchion cap to fit 22.2mm (7/8") ID tube.

The RF1694-2 life line cushion features a soft polyethylene cover for maximum comfort and a PVC inner tube to eliminate abrasion of the cushion on life lines. This, combined with the use of UV resistant materials ensures a long service life. The screw-on end caps allow easy fitting and the length can be tailored to suit.

Pelican hooks are designed for life line applications only. The sliding sleeve version, manufactured from Stainless Steel, offers wide opening, and quick release and tensioning. The threaded sleeve version, manufactured from Brass and Stainless Steel, offers secure threaded locking.

The stanchion block, RF3, is an excellent way of lifting furling lines off the deck and leading them aft. The ball bearing sheave, suitable for up to 12mm (1/2") line, ensures that friction is kept to a minimum. Designed for 25mm (1") stanchions.

PRODUCT No.	DESCRIPTION	WIRE DIAM.		BL		WEIGHT	
		mm	(in.)	kg	(lb)	g	(oz)
RF98-05	Pelican hook, sliding sleeve, swage end	-	(5/32)	450	(990)	112	(4.0)
RF98-06	Pelican hook, sliding sleeve, swage end	-	(3/16)	450	(990)	130	(4.6)
RF98M04	Pelican hook, sliding sleeve, swage end	4	-	450	(990)	112	(4.0)
RF98M05	Pelican hook, sliding sleeve, swage end	5	-	450	(990)	130	(4.6)
RF99	Pelican hook, sliding sleeve, 6.4mm (1/4") diam. eye end			450	(990)	115	(4.1)
RF198-05	Pelican hook, threaded sleeve, swage end	-	(5/32)	500	(1100)	80	(2.8)
RF198-06	Pelican hook, threaded sleeve, swage end	-	(3/16)	500	(1100)	90	(3.2)
RF198M04	Pelican hook, threaded sleeve, swage end	4	-	500	(1100)	80	(2.8)
RF198M05	Pelican hook, threaded sleeve, swage end	5	-	500	(1100)	90	(3.2)
RF199	Pelican hook, threaded sleeve, 6.4mm (1/4") diam. eye end			500	(1100)	75	(2.7)
RF1695-45	Tapered stanchion life line holes at 225mm (9") & 450mm (18") from base					390	(13.8)
RF1695-61	Tapered stanchion life line holes at 305mm (12") & 610mm (24") from base					530	(18.7)
RF1695-75	Tapered stanchion life line holes at 250mm (9 7/8"), 500mm (19 3/4") & 750mm (29 9/16") from base					650	(22.9)
RF1696-05	Stanchion base, 5° off vertical					250	(8.8)
RF1696-90	Stanchion base, Vertical					250	(8.8)
RF3	Stanchion block. Designed for leading headsail furling lines back to the cockpit					30	(1.1)
PNP54	Stanchion cap to suit 22.2mm (7/8") ID tube					12	(0.4)
PNP209GRN	Spreader / life line roller. Green					38	(1.3)
PNP209R	Spreader / life line roller. Red					38	(1.3)
RF1694-2	Life Line Cushion. OD50mm (2") x ID 9.5mm (3/8") x 2m (6ft 6") long. Complete with 2m (6ft 6") of soft polyethylene cushion tube, PVC inner tube and 2 screw-on end caps					500	(17.7)
RF1694-C	End cap only to suit RF1694-2					10	(0.4)