



RF60100  
RF60100L



RF60200



RF60300



RF60110



RF60210



RF60310

**FEATURES**

- ▶ Low friction, 2-stage ball bearing system provides consistent performance over the full load range.
- ▶ High static and dynamic load capacity.
- ▶ Light weight.
- ▶ Head posts of swivel blocks can be locked at 0 or 90 degrees.
- ▶ Shackles are forged grade 316 stainless steel.
- ▶ Cheek cut-outs for easy bearing maintenance.
- ▶ Removable becket pins allow lines to be spliced prior to fitting.
- ▶ Blocks can be disassembled for servicing or customisation.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm (in.)	MAX. ROPE mm (in.)	PIN DIAM. mm (in.)	M.W.L. kg (lb)	B.L. kg (lb)	WEIGHT g (oz)
<b>BB Ball Bearing</b>							
RF60100	Single block	60 (2 3/8)	10 (3/8)	6 (1/4)	600 (1320)	1500 (3310)	156 (5.5)
RF60100L	Single block, light load	60 (2 3/8)	10 (3/8)	5 (3/16)	300 (660)	1000 (2200)	129 (4.5)
RF60110	Single block, becket	60 (2 3/8)	10 (3/8)	6 (1/4)	600 (1320)	1500 (3310)	169 (6.0)
RF60200	Double block	60 (2 3/8)	10 (3/8)	6 (1/4)	750 (1650)	1500 (3310)	248 (8.7)
RF60210	Double block, becket	60 (2 3/8)	10 (3/8)	6 (1/4)	750 (1650)	1500 (3310)	263 (9.3)
RF60300	Triple block	60 (2 3/8)	10 (3/8)	6 (1/4)	750 (1650)	1500 (3310)	332 (11.7)
RF60310	Triple block, becket	60 (2 3/8)	10 (3/8)	6 (1/4)	750 (1650)	1500 (3310)	344 (12.1)


**RF60500**

**RF60510**

**RF60174**

4 x 5mm (3/16")


**RF60000**

3 x 6mm (1/4")



5 x 6mm (1/4")

**RF60151**


5 x 6mm (1/4")

**RF60251**
**FEATURES**

- ▶ Pivoting Lead blocks maintain alignment and keep lines as close to the deck as possible.
- ▶ Foot block has through-hub mounting for maximum strength and can be stacked to create a double (total block load same as single, maximum load on top sheave not to exceed 50% of total block load).

**APPLICATIONS**

- ▶ Mainsheet and Spinnaker sheets on sportsboats to 10m (33').
- ▶ Halyard, Vang and Backstay applications on boats to 9m (30').
- ▶ Various control line applications on larger yachts.

**MATERIALS**

- ▶ Carbon black Acetal ball bearings.
- ▶ U.V. stabilised Acetal sheaves.
- ▶ Alloy cheeks.
- ▶ Grade 316 stainless steel forged shackle.
- ▶ Grade 316 stainless steel hub.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
<b>Ball Bearing</b>													
RF60000	Sheave	60	(2 3/8)	10	(3/8)	-	-	600	(1320)	-	-	50	(1.8)
RF60151	Foot block, single	60	(2 3/8)	10	(3/8)	-	-	600	(1320)	1500	(3310)	116	(4.1)
RF60174	Pivoting low lead block	60	(2 3/8)	10	(3/8)	-	-	300	(660)	1000	(2200)	125	(4.4)
RF60251	Foot block, double	60	(2 3/8)	10	(3/8)	-	-	600*	(1320)*	1500*	(3310)*	172	(6.1)
RF60500	Fiddle block	60	(2 3/8)	10	(3/8)	6	(1/4)	600	(1320)	1500	(3310)	204	(7.2)
RF60510	Fiddle block, becket	60	(2 3/8)	10	(3/8)	6	(1/4)	600	(1320)	1500	(3310)	216	(7.6)

\* Total block load. Maximum load on top sheave not to exceed 50% of total block load.