



**FEATURES**

- ▶ High static and dynamic load capacity achieved with alloy sheaves, Torkon® needle rollers for axial loads, Acetal ball bearings for side thrust loads.
- ▶ Head posts of swivel blocks can be locked at 0 or 90 degrees.
- ▶ Shackles are forged grade 316 stainless steel.

**APPLICATIONS**

- ▶ Cheek cut-outs for easy bearing maintenance.
- ▶ Removable becket pins allow lines to be spliced prior to fitting.
- ▶ Upright lead blocks keep lines as close to the deck as possible.
- ▶ Blocks can be disassembled for servicing.

- ▶ Halyard block has a removable pin for attachment to deck padeyes or mast collar.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
 <b>Roller Ball Bearing</b>													
RF68100	Single block	60	(2 3/8)	14	(9/16)	8	(5/16)	1500	(3310)	3000	(6610)	315	(11.1)
RF68108	Halyard block	60	(2 3/8)	14	(9/16)	8	(5/16)	1500	(3310)	3000	(6610)	165	(5.8)
RF68110	Single block, becket	60	(2 3/8)	14	(9/16)	8	(5/16)	1500	(3310)	3000	(6610)	347	(12.2)
RF68140	Stand-up block	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	465	(16.4)
RF68171	Upright lead block	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	222	(7.8)
RF68202	Double block, non-swivel head	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	440	(15.5)
RF68212	Double block, becket, non-swivel head	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	475	(16.8)
 <b>All Purpose</b>													
RF61100	Single block	60	(2 3/8)	14	(9/16)	8	(5/16)	1000	(2200)	3000	(6610)	285	(10.1)
RF61171	Upright lead block	60	(2 3/8)	14	(9/16)	-	-	1000	(2200)	3000	(6610)	205	(7.2)
RF61176	Over-the-top block	60	(2 3/8)	14	(9/16)	-	-	1000	(2200)	3000	(6610)	215	(7.6)



Suits RF68174, RF68151, RF68251, RF61151

**FEATURES**

- ▶ Foot blocks are available in single or double versions, with through-hub mounting for maximum strength.
- ▶ Jammers are a convenient way to temporarily lock off a control line – kit suits foot blocks and pivoting lead blocks.
- ▶ Padeyes and stand-up springs add functionality to the range.

**APPLICATIONS**

- ▶ Mainsheet and Spinnaker sheets on boats to 11m (36').
- ▶ Halyard, Vang and Backstay applications on boats to 12m (40').
- ▶ General control line applications on larger yachts.

**MATERIALS**

- ▶ Alloy sheave and cheek plates.
- ▶ Torlon® needle rollers.
- ▶ Carbon black Acetal ball bearings.
- ▶ Grade 316 stainless steel head post and forged shackle.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
<b>RB</b> Roller Ball Bearing													
RF68000	Sheave	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	-	-	85	(3.0)
RF68000W	Sheave, wide	60	(2 3/8)	25	(1)	-	-	1150	(2540)	-	-	128	(4.5)
RF68151	Foot block, single	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	194	(6.8)
RF68174	Pivoting low lead block	60	(2 3/8)	14	(9/16)	-	-	1500	(3310)	3000	(6610)	341	(12.0)
RF68251	Foot block, double	60	(2 3/8)	14	(9/16)	-	-	1500*	(3310)*	3000*	(6610)*	291	(10.3)
RF68300	Triple block, swivel head	60	(2 3/8)	14	(9/16)	8	(5/16)	1500	(3310)	3000	(6610)	635	(22.4)
<b>AP</b> All Purpose													
RF61000	Sheave	60	(2 3/8)	14	(9/16)	-	-	1000	(2210)	-	-	67	(2.4)
RF61151	Foot block, single	60	(2 3/8)	14	(9/16)	-	-	1000	(2210)	3000	(6610)	178	(6.3)
<b>Accessories</b>													
RF324	Stand-up spring kit	-	-	-	-	-	-	-	-	-	-	80	(2.8)
RF1391	Jammer kit	-	-	-	-	-	-	-	-	-	-	90	(3.2)
RF2432-09	Padeye	-	-	-	-	-	-	-	-	4000	(8820)	105	(3.7)
RF2433-09	Padeye, removable	-	-	-	-	-	-	-	-	4000	(8820)	285	(10.1)

\* Total block load. Maximum load on top sheave not to exceed 50% of total block load.