



RF108100



RF108110



RF108202



RF108140



RF108108

4 x 6mm (1/4")


FEATURES

- ▶ High static and dynamic load capacity achieved with alloy sheaves, Torklon® needle rollers for axial loads, Acetal ball bearings for side thrust loads.
- ▶ Head posts of swivel blocks can be locked at 0 or 90 degrees.
- ▶ Shackles are forged grade 316 stainless steel.

- ▶ Cheek cut-outs for easy bearing maintenance.
- ▶ Removable becket pins allow lines to be spliced prior to fitting.
- ▶ Halyard block has a removable pin for attachment to deck padeyes or mast collar.
- ▶ Blocks can be disassembled for servicing.

APPLICATIONS

- ▶ Halyard block has a removable pin for attachment to deck padeyes or mast collar.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
 Roller Ball Bearing													
RF108100	Single block	100	(4)	14	(9/16)	8	(5/16)	2200	(4850)	4400	(9700)	640	(22.6)
RF108108	Halyard block	100	(4)	14	(9/16)	12	(1/2)	2200	(4850)	4400	(9700)	445	(15.7)
RF108110	Single block, becket	100	(4)	14	(9/16)	8	(5/16)	2200	(4850)	4400	(9700)	710	(25.0)
RF108140	Stand-up block	100	(4)	14	(9/16)	-	-	2000	(4410)	4000	(8820)	773	(27.3)
RF108202	Double block, non-swivel head	100	(4)	14	(9/16)	-	-	2200	(4850)	4400	(9700)	1026	(36.2)



FEATURES

- ▶ Upright lead blocks, typically used for halyards at the mast base, keep lines close to the deck.
- ▶ Foot blocks are available in single or double versions, with through-hub mounting for maximum strength.
- ▶ Padeyes and stand-up springs add functionality to the range.

APPLICATIONS

- ▶ Mainsheet, Halyard and Spinnaker sheets on boats to 16m (53').
- ▶ Permanent backstay applications on boats to 12m (40').
- ▶ General control line applications on larger yachts.

MATERIALS

- ▶ Alloy sheave and cheek plates.
- ▶ Torlon® needle rollers.
- ▶ Carbon black Acetal ball bearings.
- ▶ Grade 316 stainless steel head post and forged shackle.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm (in.)	MAX. ROPE mm (in.)	M.W.L. kg (lb)	B.L. kg (lb)	WEIGHT g (oz)
RB Roller Ball Bearing						
RF108000	Sheave	100 (4)	14 (9/16)	2900 (6390)	- -	262 (9.2)
RF108000F	Sheave to suit foot block	100 (4)	14 (9/16)	3850 (8490)	7890 (17390)	275 (9.7)
RF108000W	Sheave, wide	100 (4)	25 (1)	3900 (8600)	- -	497 (17.5)
RF108151	Foot block, single	100 (4)	14 (9/16)	3850 (8490)	- -	480 (16.9)
RF108171	Upright lead block	100 (4)	14 (9/16)	2200 (4850)	4400 (9700)	517 (18.2)
RF108251	Foot block, double	100 (4)	14 (9/16)	3850* (8490)*	7890* (17390)*	850 (30.0)
Accessories						
RF324	Stand-up spring kit	- -	- -	- -	- -	80 (2.8)
RF1391	Jammer kit	- -	- -	- -	- -	90 (3.2)
RF2432-09	Padeye	- -	- -	- -	4000 (8820)	105 (3.7)
RF2433-09	Padeye, removable	- -	- -	- -	4000 (8820)	285 (10.1)

* Total block load. Maximum load on top sheave not to exceed 50% of total block load.