



RF128100



RF128110




RF128140

→ | ←
4 x 8mm (5/16")

FEATURES

- ▶ High static and dynamic load capacity achieved with alloy sheaves, Torlon® needle rollers for axial loads, Acetal ball bearings for side thrust loads.
- ▶ Head posts of swivel blocks can be locked at 0 or 90 degrees.
- ▶ Shackles are forged grade 316 stainless steel.
- ▶ Cheek cut-outs for easy bearing maintenance.
- ▶ Removable becket pin allows lines to be spliced prior to fitting.
- ▶ Blocks can be disassembled for servicing.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
 Roller Ball Bearing													
RF128100	Single block	125	(5)	16	(5/8)	10	(3/8)	3750	(8270)	7500	(16530)	1105	(39.0)
RF128110	Single block, becket	125	(5)	16	(5/8)	10	(3/8)	3750	(8270)	7500	(16530)	1160	(40.9)
RF128140	Stand-up block	125	(5)	16	(5/8)	-	-	2500	(5510)	5000	(11020)	1446	(51.0)



FEATURES

- ▶ Upright lead blocks, typically used for halyards at the mast base, keep lines close to the deck.
- ▶ Foot blocks are available in single or double versions, with through-hub mounting for maximum strength.
- ▶ Padeyes and stand-up springs add functionality to the range.

APPLICATIONS

- ▶ Mainsheet on boats to 18m (60').
- ▶ Halyard and Spinnaker sheets on boats to 20m (65').
- ▶ Genoa foot blocks on boats to 18m (60').

MATERIALS

- ▶ Alloy sheave and cheek plates.
- ▶ Torlon® needle rollers.
- ▶ Carbon black Acetal ball bearings.
- ▶ Grade 316 stainless steel head post and forged shackle.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
RB Roller Ball Bearing											
RF128000	Sheave	125	(5)	16	(5/8)	4900	(10800)	-	-	448	(15.8)
RF128000F	Sheave to suit foot block	125	(5)	16	(5/8)	4900	(10800)	-	-	470	(16.6)
RF128000W	Sheave, wide	125	(5)	32	(1 1/4)	6650	(14660)	-	-	817	(28.8)
RF128151	Foot block, single	125	(5)	16	(5/8)	4900	(10800)	9800	(21610)	850	(30.0)
RF128171	Upright lead block	125	(5)	16	(5/8)	3750	(8270)	7500	(16530)	777	(27.4)
RF128251	Foot block, double	125	(5)	16	(5/8)	4900*	(10800)*	9800*	(21610)*	1520	(53.6)
Accessories											
RF325	Stand-up spring kit	-	-	-	-	-	-	-	-	180	(6.3)
RF2432-10	Padeye	-	-	-	-	-	-	5000	(11020)	190	(6.7)
RF2433-10	Padeye, removable	-	-	-	-	-	-	5000	(11020)	550	(19.4)

* Total block load. Maximum load on top sheave not to exceed 50% of total block load.