



RF158100



RF158110




RF158140

4 x 10mm (3/8")

FEATURES

- ▶ High static and dynamic load capacity achieved with alloy sheaves, Torlon® needle rollers for axial loads, Acetal ball bearings for side thrust loads.
- ▶ Head posts of swivel blocks can be locked at 0 or 90 degrees.
- ▶ Shackles are forged grade 316 stainless steel.
- ▶ Cheek cut-outs for easy bearing maintenance.
- ▶ Removable becket pin allows lines to be spliced prior to fitting.
- ▶ Blocks can be disassembled for servicing.
- ▶ Upright lead blocks, typically used for halyards at the mast base, keep lines close to the deck.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		PIN DIAM.		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
 Roller Ball Bearing													
RF158100	Single block	150	(6)	20	(3/4)	12	(1/2)	5600	(12350)	11200	(24690)	1936	(68.3)
RF158110	Single block, becket	150	(6)	20	(3/4)	12	(1/2)	5600	(12350)	11200	(24690)	1984	(70.0)
RF158140	Stand-up block	150	(6)	20	(3/4)	-	-	3000	(6610)	6000	(13230)	2190	(77.2)



FEATURES

- ▶ Foot blocks are available in single or double versions, with through-hub mounting for maximum strength.

APPLICATIONS

- ▶ Mainsheet on boats to 23m (75').
- ▶ Halyard and Spinnaker sheets on boats to 25m (82').
- ▶ Genoa foot blocks on boats to 23m (75').

MATERIALS

- ▶ Alloy sheave and cheek plates.
- ▶ Torton® needle rollers.
- ▶ Carbon black Acetal ball bearings.
- ▶ Grade 316 stainless steel head post and forged shackle.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm (in.)	MAX. ROPE mm (in.)	M.W.L. kg (lb)	B.L. kg (lb)	WEIGHT g (oz)
RB Roller Ball Bearing						
RF158000	Sheave	150 (6)	20 (3/4)	6900 (15210)	- -	739 (26.1)
RF158000W	Sheave, wide	150 (6)	32 (1 1/4)	8100 (17860)	- -	1164 (41.1)
RF158151	Foot block, single	150 (6)	20 (3/4)	6900 (15210)	13800 (30420)	1483 (52.3)
RF158171	Upright lead block	150 (6)	20 (3/4)	5500 (12130)	11000 (24250)	1714 (60.5)
RF158251	Foot block, double	150 (6)	20 (3/4)	6900* (15210)*	13800* (30420)*	2642 (93.2)

Accessories

RF2432-12	Padeye	-	-	-	6000 (13230)	300 (13.8)
RF2433-12	Padeye, removable	-	-	-	8000 (17640)	1025 (36.2)

* Total block load. Maximum load on top sheave not to exceed 50% of total block load.