



FEATURES

- ▶ Deck organisers are an effective means of deflecting halyards and control lines to winches, stoppers and cleats.
- ▶ All-purpose bearing system provides maximum static load capacity.
- ▶ Light weight design with check cut-outs for easy bearing maintenance.
- ▶ Through-hub mounting for maximum strength.

- ▶ All sizes can be stacked to create double versions - M.W.L. of the top sheaves must not exceed 50% of the total block load rating.

- ▶ Line deflection on larger yachts (depending on load and angle of deflection).

APPLICATIONS

- ▶ Series 40 - Halyard and Control line deflection on boats to 11m (36').
- ▶ Series 60 - Halyard and Control line deflection on boats to 14m (46').

MATERIALS

- ▶ Alloy upper and lower cheek plates.
- ▶ U.V. stabilised Acetal sheaves.
- ▶ Grade 316 stainless steel hubs.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.		MAX. ROPE		LENGTH		HOLE SPACING		M.W.L. (per sheave)		B.L. (per sheave)		WEIGHT	
		mm	(in.)	mm	(in.)	mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
AP All Purpose															
RF41821	Double sheave organiser	40	(1 5/8)	12	(1/2)	116	(4 9/16)	48.5	(1 29/32)	500	(1100)	1000	(2200)	101	(3.6)
RF41831	Triple sheave organiser	40	(1 5/8)	12	(1/2)	164	(6 15/32)	48.5	(1 29/32)	500	(1100)	1000	(2200)	142	(5.0)
RF41841	Quadruple sheave organiser	40	(1 5/8)	12	(1/2)	213	(8 13/32)	48.5	(1 29/32)	500	(1100)	1000	(2200)	185	(6.5)
RF61821	Double sheave organiser	60	(2 3/8)	14	(9/16)	164	(6 15/32)	70	(2 3/4)	1000	(2200)	2000	(4410)	271	(9.6)
RF61831	Triple sheave organiser	60	(2 3/8)	14	(9/16)	234	(9 7/32)	70	(2 3/4)	1000	(2200)	2000	(4410)	392	(13.8)
RF61841	Quadruple sheave organiser	60	(2 3/8)	14	(9/16)	304	(11 31/32)	70	(2 3/4)	1000	(2200)	2000	(4410)	511	(18.0)