


**FEATURES**

- ▶ Low profile, lightweight alloy cars and end caps.
- ▶ Twin rows of recirculating Torlon® ball bearings provide smooth, low friction performance under load.
- ▶ Loop and fork style fittings are easily added for bucket and control line block attachment.

- ▶ Compact sheave arrangements for neat, low profile control line purchase systems. Control sheaves are 24mm (15/16") diameter and suit up to 6mm (1/4") rope.
- ▶ Cleats, fairleads and cheek blocks can be mounted directly on deck or cockpit sides to complete the control line systems.

**APPLICATIONS**

- ▶ Dinghy and catamaran traveller and jib sheet systems.

**MATERIALS**

- ▶ Alloy track, car bodies and end caps.
- ▶ Torlon® ball bearings.
- ▶ Grade 316 stainless steel fixtures.

▶ **TRACK FASTENINGS** – 4mm (5/32") countersunk fasteners at 50mm (1 31/32") centres

PRODUCT No.	DESCRIPTION	LENGTH		WIDTH		M.W.L.		B.L.		WEIGHT	
		mm	(in.)	mm	(in.)	kg	(lb)	kg	(lb)	g	(oz)
<b>BB Ball Bearing</b>											
RC1141J	Track joiner	40	(1 9/16)	-	-	-	-	-	-	1	(0.1)
RC11401	Car, 2 mounting holes, 35mm (1 3/8") hole spacing	68	(2 11/16)	41	(1 5/8)	150	(330)	400	(880)	51	(1.8)
RC11402	Car, pivoting shackle top	47	(1 7/8)	41	(1 5/8)	125	(280)	400	(880)	48	(1.7)
RC11403	Car, pivoting shackle top, 2 mounting screws	78	(3 1/16)	41	(1 5/8)	180	(400)	400	(880)	91	(3.2)
RC1140-1.0	Track, black	996	(39 1/4)	14	(9/16)	-	-	-	-	230	(8.1)
RC1140-1.5	Track, black	1496	(59)	14	(9/16)	-	-	-	-	345	(12.2)
RC1140-2.0	Track, black	1996	(78 5/8)	14	(9/16)	-	-	-	-	460	(16.2)
RC1140-3.0	Track, black	2996	(118)	14	(9/16)	-	-	-	-	690	(24.3)
RC1140-6.0	Track, black	5996	(236 1/4)	14	(9/16)	-	-	-	-	1380	(48.7)
RC11410	Car, saddle top, single control sheaves	68	(2 11/16)	41	(1 5/8)	150	(330)	400	(880)	89	(3.1)
RC11480	End cap, plastic	28	(1 1/8)	20	(25/32)	-	-	-	-	6	(0.2)
RC11484	Control end, single sheave	52	(2)	33	(1 5/16)	-	-	-	-	15	(0.5)
RC11485	Control end, single sheave & becket	64	(2 1/2)	33	(1 5/16)	-	-	-	-	23	(0.8)
<b>Accessories</b>											
RF134	Saddle, control line termination point	-	-	-	-	-	-	-	-	5	(0.2)
RF1050	Control becket, 8mm (5/16") eye, suits RC11403	-	-	-	-	-	-	-	-	6	(0.2)
RF1052	Control becket fork, 5mm (3/16") pin, suits RC11403	-	-	11	(7/16)	-	-	-	-	9	(0.3)
RF5000	Cleat, suits 2mm - 8mm (3/32" - 5/16") rope	-	-	-	-	120	(260)	240	(530)	20	(0.7)
RF5005	Fairlead, suits RF5000 cleat	-	-	-	-	-	-	-	-	7	(0.2)
RF20151	Cheek block, for leading control lines	-	-	-	-	250	(550)	550	(1210)	14	(0.5)
RF20151A	Cheek block rivet mount, for leading control lines	-	-	-	-	200	(440)	550	(1210)	17	(0.6)